適用規格追加のご案内

HG2G/HG4G形プログラマブル表示器

HG2G/HG4G形プログラマブル表示器の適用規格にUL HazLoc (ANSI/ISA 12.12.01)が追加されましたのでご案内いたします。

対象機種及び実施時期

機　　種	形　　番	変更時期
HG2G形プログラマブル表示器	HG2G-5FT22TF-＊	2012年12月
	HG2G-5ST22TF-＊ HG2G-5ST22VF-＊	
HG4G形プログラマブル表示器	HG4G-CJT22MF-B HG4G-CJT22TF-B	

＊・・・ベゼル色(W:ライトグレー/B:ダークグレー/S:シルバー)

※上記機種を基本としたカスタム仕様品も含みます。

変更内容

適用規格の追加に伴い、取扱説明書及び本体ラベルの記載を変更いたします。
本体ラベルの変更は下表のとおりです。

型番	変更前	変更後
HG2G -5FT形	IDEC TYPE: HG2G-5FT22TF-W S/N: 00000-00000 RATING: 24V DC 19W(max) MAX. TEMP.: 50℃ MADE IN JAPAN FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE FOR CLASS 2 SOURCE ONLY 67T0 IND.CONT.EQ. c UL US LISTED IDEC CORPORATION	IDEC TYPE: HG2G-5FT22TF-W S/N: 00000-00000 24V DC 19W, CLASS 2 MAX. TEMP.: 50℃ TEMPERATURE CODE: T5 MADE IN JAPAN CLASS Ⅰ DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE. FOR CLASS 2 SOURCE ONLY. 478N IND.CONT.EQ. FOR HAZ.LOC. c UL US LISTED IDEC CORPORATION
HG2G -5ST形	IDEC MICRO/I TYPE: HG2G-5ST22TF-W S/N: 00000-00000 RATING: 12 / 24 VDC 8W (MAX.) MAX. TEMP.: 50℃ MADE IN JAPAN FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE FOR CLASS 2 SOURCE ONLY 67T0 IND.CONT.EQ. c UL US LISTED IDEC CORPORATION	IDEC MICRO/I TYPE: HG2G-5ST22TF-W S/N: 00000-00000 12 to 24 V DC 8W, CLASS 2 MAX. TEMP.: 50℃ TEMPERATURE CODE: T5 CLASS Ⅰ DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1 ENCLOSURE. FOR CLASS 2 SOURCE ONLY. MADE IN JAPAN 478N IND.CONT.EQ. FOR HAZ.LOC. c UL US LISTED IDEC CORPORATION
HG4G形	IDEC TYPE: HG4G-CJT22TF-B S/N: 00000-00000 RATING: 24V DC 27W(max) MAX. TEMP.: 50℃ FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY OR TYPE 13 ENCLOSURE FOR CLASS 2 SOURCE ONLY MADE IN JAPAN c UL US LISTED IDEC CORPORATION	IDEC MADE IN JAPAN TYPE: HG4G-CJT22TF-B S/N: 00000-00000 24V DC 27W, CLASS 2 MAX. TEMP.: 50℃ TEMPERATURE CODE: T6 TIGHTENING TORQUE FOR MOUNTING: 0.5 to 0.6 Nm ONLY. FOR INSTALLATION CLASS Ⅰ DIV.2 GROUPS A, B, C, D. FOR USE ON A FLAT SURFACE OF A TYPE 1, TYPE 4X INDOOR USE ONLY OR TYPE 13 ENCLOSURE. FOR CLASS 2 SOURCE ONLY USE MIN. 60℃ WIRE, COPPER WIRE ONLY. c UL US LISTED IDEC CORPORATION

※Class Ⅰ、Division 2、Groups A、B、C及び、D ハザーダスロケーション
または、ノンハザーダスロケーションでの使用のみ適合しています。
その他仕様、形番、価格の変更はありません。